



REVOL LTD Manufacturers of Revol / Voler Industrial Oils and Greases

Registered Office: SAMSON CLOSE, KILLINGWORTH, NEWCASTLE UPON TYNE. NE12 6DZ UK
Tel: +44(0)191 2684555 Fax: +44(0)191 2160004 [E-mail:sales@revol.co.uk](mailto:sales@revol.co.uk)

REVOL VALVE LUBRICANT - CSG

DESCRIPTION:

Revol Valve Lubricant – CSG is a purpose made product designed for Oilfield and Petrochemical applications. Revol Valve Lubricant – CSG has been formulated to provide lubrication even under the severe service conditions encountered in modern gate valves employed in the Oilfield including Pipelines and Refineries.

Revol Valve Lubricant – CSG is resistant to; Brine, Steam, Condensate, many chemicals and most refinery gases. The product contains a high percentage of solid lubricants which provide outstanding load carrying and long term lubrication performance.

APPLICATIONS:

Modern Oilfield and Refinery Valves – To be used in accordance with Valve manufacturers directions.

Alternative Revol products are available for higher temperature Valve Lubrication and for applications requiring a higher level of chemical resistance.

BENEFITS:

Purpose-Made Product

Good Chemical Resistance.

Non Melting

Highly Adhesive

Biodegradable Non-Toxic Product, can be recommended for use in many environmentally sensitive areas.

High Percentage of Solid Lubricant provide outstanding lubrication and component protection

TYPICAL PHYSICAL CHARACTERISTICS:

Appearance	Smooth Adhesive Grease
Colour	Black
NLGI Classification	0
Worked Penetration (ASTM D-217)	355 – 385
Temperature Range	-30°C to +120°C
Drop Point (ASTM D-566)	None – Infusible Product
Base Oil	Vegetable Oil
Thickening Agent	Non-Soap, Non-Clay Revol Thickener System.

PACKAGING:

12.5 Kilo Kegs, 50 Kilo Kegs, 180 Kilo Barrels. (Other pack sizes may be available by request).